

## **DEX PREP**

A timber brightener that cleans and brightens weathered and grey timber and assists in opening the timber grain to allow penetration.

#### **Advantages**

- Highly concentrated
- Used neat it will kill mould spores

#### **Typical Applications**

Grey or dirty timber over 12 months old.

#### Coverage

6-8m<sup>2</sup> per litre

### **Application Method**

By brush, hose.

Good preparation is key to a professional looking, long lasting finish:

- 1. Remove surface dirt by sweeping or hosing.
- 2. Shake DEX PREP thoroughly and mix in a plastic container or bucket.
  - a. General cleaning: mix one part DEX PREP to 5 parts water
  - b. Severe staining: apply neat.
- 3. Wet the surface to be cleaned.
- 4. Apply mixture generously with a scouring or scrubbing brush and scrub timber thoroughly.
- 5. Leave for 10-15 minutes.
- 6. Rinse off using a garden hose, or a high pressure water cleaner for large areas or badly discoloured timber. Use a sponge and water for interior surfaces.

Note: Do not "spot clean" as this may result in a patchy appearance, clean the whole area at the same time. DEX PREP may not remove old deep seated fungal stains and timber marking dyes. For best results apply DEX PREP to cool surfaces out of direct sunlight. Do not allow to dry on the surface before removal.

Failure to remove the cleaning solution residue may result in timber discolouration under clear finishes or early failure of the coating due to changed pH.

DEX PREP (4930) Issued 03/06/2019 Page 1

The information in this data sheet represents typical values. Application variables affect product performance therefore this information should be used as a guide. The user must satisfy themselves as to the suitability of this product for their requirements. Mirotone assumes no liability for use of this information.

# **DEX PREP**



A timber brightener that cleans and brightens weathered and grey timber and assists in opening the timber grain to allow penetration.

DEX PREP is mildly acidic, avoid contact with painted metal surfaces and vegetation. Rinse thoroughly if contact occurs.

Specifications	Drying (if coating with):	Oil based paints or stains - allow to dry for 2 to 3 days before painting coatings.  Water based paints or stains - apply as soon as the timber is dry.
Properties	Finish	Not Required.
	VOC Level	Not Required.
	Thinner	Not required.
	Pack Sizes	1L, 4L, 10L.
	Product Code	4930.
	Clean Up	Water clean-up.

#### **Health & Safety**

Before handling, refer to the Safety Data Sheet (SDS) for health and safety information. Ensure that all people using this product have read and understood this data sheet, the associated SDS and packaging label before using this product.